

# United States Patent [19]

Soirinsuo et al.

[11] Patent Number:

6,084,855

[45] Date of Patent:

Jul. 4, 2000

[54] METHOD AND APPARATUS FOR PROVIDING FAIR TRAFFIC SCHEDULING AMONG AGGREGATED INTERNET PROTOCOL FLOWS

[75] Inventors: Timo Soirinsuo, Cambridge, Mass.;
Outi Markki, Espoo, Finland

[73] Assignee: Nokia Telecommunications, OY, Espoo, Finland

[21] Appl. No.: 08/802,451
[22] Filed: Feb. 18, 1997

[56] References Cited

### U.S. PATENT DOCUMENTS

5,278,830	1/1994	Kudo 370/412
5,499,238	3/1996	Shon.
		Shtayer et al 395/200.11
5,828,653	10/1998	Goss.
5,872,771	2/1999	Park et al 370/252

### FOREIGN PATENT DOCUMENTS

0 763 915 A2 3/1997 European Pat. Off. .

WO 97/13346 4/1997 WIPO . WO 98/26510 6/1998 WIPO .

## OTHER PUBLICATIONS

P. Newman et al., "Flow Labelled IP: A Connectionlness Approach to ATM", Proc. IEEE Infocom, Mar. 1996, Ch. 5-6, pp. 1255-1260.

Primary Examiner—Ajit Patel Attorney, Agent, or Firm—Altera Law Group, LLC

7] ABSTRACT

A method and apparatus is disclosed for providing fair traffic scheduling of L2 connections based on the number of IP flows and a priority coefficient for flow groups in the L2 connection. IP flows are scheduled according to a priority coefficient. The system identifies a number of IP flows for a plurality of connections, assigns a priority coefficient for each of the IP flows and schedules the IP flows according to the priority coefficient. The assignment of a priority coefficient results in a probability  $P_i$  that a data unit belonging to a flow carried over connection  $A_i$  will be selected for forwarding as defined by  $\sigma_i^* * x_i / \Sigma(x_1 \dots x_n)$ ,  $i = \{1, 2, \dots n\}$ , where  $x_i$  is the number of flows carried over connection. The relationship between the number of flows  $x_i$  and the priority  $\sigma_i$  is defined by  $\sum_{(e-1-n)} (\sigma_i^* * x_i) / \sum_{(i-1-n)} x_i = 1$ .

### 32 Claims, 6 Drawing Sheets

